

NPH1 Pushbutton Box

1. General information

Electric ratings: AC50/60Hz, AC415V/DC250V;

Degree of protection: IP54/IP40 Standard: IEC/EN60947-5-1





4. NPH1 Enckosure

Bare box with one hole

	Model		Specifications
		Color	Protection degree
	NPH1-10J		IP54
	NPH1-1J		IP40
0	NPH1-10		IP54
	NPH1-1		IP40

Bare box with two hole

	N/I and all		Specifications
	Model	Color	Protection degree
	NPH1-20J		IP54
	NPH1-2J		IP40
0	NPH1-20		IP54
	NPH1-2	IP40	

2. Working & mounting conditions

- 2.1 Ambient temperature is -5°C~+40°C, the average temperature during 24 hours couldn't exceed +35°C.
- 2.2 Altitude: ≤2000m.
- 2.3 Atmosphere condition:
 Relative humidity of the atmosphere
 couldn't exceed 50%
 when the highest temperature is +40°C;
 much higher relative humidity is allowable
 under the condition of lower temperature,
 for example, when the temperature reaches +20°C,
 the relative humidity is up to 90%. As for dews,
 which contingently appear
 due to change of temperature,
 special steps should be taken.
- 2.4 Pollution grade: 3
- 2.5 Installation category: II

3. Technical data

- 3.1 Conventional heating current Ith: 10A
- 3.2 Refer to table below, for ratings under different utilization categories.

۸	AC-15 Rated operational voltage, V		240	120
AC-15	Rated operational current, V	1.9	3	6
DC 13	Rated operational voltage, V	250	125	-
DC-13	Rated operational current, V	0.27	0.55	-

Life

Electric life: Flush-headed and mushroom-headed type: $AC.5\times10^{5}$ operations, $DC2.5\times10^{5}$ operations;

other type: 1×10^5 operations;


Mechanical life: flush-headed and mushroom-headed type:

1 million operations,

button with light: 3×10^6 operations; other type: 1×10^5 operations

Rated operational voltage	Rated operational current
AC/DC 6V, 12V, 24V, 36V	≤20mA
AC 110V~220V	≤20mA

Dimension (mm)



Bare box with three hole


NAI - I		Specifications
Model	Color	Protection degree
NPH1-30J		IP54
NPH1-3J		IP40
NPH1-30		IP54
NPH1-3		IP40

Pushbuttons & Indicator Lights & buzzers **Pushbuttons**




Dimension (mm)

Bare box with two hole




Bare box with three hole



Box with one hole (with flush button)

	NA - J. I		Speci	fications	
	Model	1	 	Color	
•	NPH1-1001	1			
	NPH1-1002	1	_	•	
	NPH1-1003	_	1	•	
	NPH1-1004	_	1	•0	


Dimension (mm)



Box with one hole (with mushroom-headed button)

	B41 - 1	Specifications			
	Model			 	Color
9	NPH1-1005	φ 40	1	_	•
	NPH1-1006	φ 40	_	1	•


Dimension (mm)



Box with one hole (with selector switch)

NA - Jal	Specifications			
Model	Type of positions	1	ł	Color
NPH1-1007		1	_	•
NPH1-1008		2	_	•


Dimension (mm)



Box with one hole (with mushroom-headed button, self-locking)

	Specifications				
Model		1	ŀ	Color	
NPH1-1009	φ 40	_	1	•	
NPH1-1010	φ 60	_	1	•	

Dimension (mm)






Box with one hole (with key switch)

		Specificati	ons		
Model		Type of positions	1	þ	
NPH1-1011	φ 40	**	_	1	


Dimension (mm)



Box with two holes (with flush button)


			Specifications		
	Model	-	þ	Color	
	NPH1-2001	1	_		
	NPH1-2001	_	1		
	NPH1-2002	1	_	• 1	
			1		
	NPH1-2003	1	_	○ ←	
			1	• →	
	NIDI 11 2004	1	_	\bigcirc \uparrow	
	NPH1-2004	_	1	•	

Dimension (mm)



Box with three holes (with flush button)

				Specification	ns
	Model		þ		Color
		1	_		
	NPH1-3001	_	1		
		1	_		
		1	_		• 1
	NPH1-3002	_	1		
		1	_		•
		1	_		○ ←
		_	1		• 0
	NPH1-3003	1	_		• →
		1	_		\bigcirc \uparrow
	NPH1-3004	_	1		
		1	_		• +



Dimension (mm)

71max

